## Package: paramlink2 (via r-universe)

November 6, 2024

Type Package

Title Parametric Linkage Analysis

Version 1.0.6

Description Parametric linkage analysis of monogenic traits in medical pedigrees. Features include singlepoint analysis, multipoint analysis via 'MERLIN' (Abecasis et al. (2002) <doi:10.1038/ng786>), visualisation of log of the odds (LOD) scores and summaries of linkage peaks. Disease models may be specified to accommodate phenocopies, reduced penetrance and liability classes. 'paramlink2' is part of the 'pedsuite' package ecosystem, presented in 'Pedigree Analysis in R' (Vigeland, 2021, ISBN:9780128244302).

License GPL-3

URL https://github.com/magnusdv/paramlink2

BugReports https://github.com/magnusdv/paramlink2/issues

**Depends** R (>= 4.1), pedtools

Imports pedprobr

Suggests spelling, testthat

Encoding UTF-8

Language en-GB

LazyData true

**Roxygen** list(markdown = TRUE)

RoxygenNote 7.3.2

**SystemRequirements** MERLIN (https://csg.sph.umich.edu/abecasis/merlin/) for multipoint linkage analysis.

**Repository** https://magnusdv.r-universe.dev

RemoteUrl https://github.com/magnusdv/paramlink2

RemoteRef HEAD

RemoteSha 243d57dc08c2a2939e30e0d0aee2a943552bb698

### Contents

| diseaseModel | <br> | <br> | <br>. 2 |
|--------------|------|------|---------|
| dominant1    | <br> | <br> | <br>. 3 |
| linkres      | <br> | <br> | <br>. 4 |
| lod          | <br> | <br> | <br>. 5 |
| lodPeaks     | <br> | <br> | <br>. 7 |
| merlinLod    | <br> | <br> | <br>. 8 |
|              |      |      |         |
|              |      |      | - 11    |

#### Index

diseaseModel Disease models for linkage analysis

#### Description

Create a disease model in form of a disModel object, for use in e.g. lod().

#### Usage

diseaseModel(model = NULL, chrom = NULL, penetrances = NULL, dfreq = NULL)

#### Arguments

| model       | An existing disModel object (to be modified by other arguments), or one of the following two-letter keywords:   |
|-------------|---|
|             | • AD = autosomal dominant   |
|             | • AR = autosomal recessive  |
|             | • XD = X-linked dominant  |
|             | • XR = X-linked recessive   |
|             | In all of the above, the disease is assumed to be fully penetrant, and with a disease allele frequency of 1e-5.   |
| chrom       | Either "AUTOSOMAL" or "X". Lower case versions are allowed and will be converted automatically.   |
| penetrances | For autosomal models, a numeric of length 3 corresponding to (f0, f1, f2), where fi is the probability of being affected given i disease alleles. It can also be a matrix with 3 columns, in which case each row represents a liability class.  |
|             | For X-linked models, a list of two vectors named male and female, of lengths 2 and 3 respectively: $(f0, f1)$ for males and $(f0, f1, f2)$ for females. Alternatively, each list entry may be a matrix or data frame (with the same number of columns) where each row represents a liability class. |
| dfreq       | A number in [0,1]: The population frequency of the disease allele.  |

#### Value

An object of class disModel, which is a list with entries chrom, penetrances and dfreq.

#### dominant1

#### See Also

lod()

#### Examples

dominant1

#### Dominant linkage analysis example

#### Description

A dataset with SNP genotypes for 14 members of a pedigree affected with a dominant disorder.

#### Usage

dominant1

#### Format

A list with 3 elements:

- ped: A pedtools::ped object describing a pedigree with 19 individuals, including genotypes for 14 members at 248 markers on Chromosome 1.
- aff: A vector indicating the affected pedigree members.
- map: A data frame with 3 columns (chrom, marker, cm) describing the centiMorgan positions of the markers.

linkres

#### Examples

```
data(dominant1)
ped = dominant1$ped
aff = dominant1$aff
model = diseaseModel("AD")
# Compute singlepoint LODs
lods = lod(ped, aff = aff, model = model)
# LOD score graph
plot(lods)
```

linkres

#### S3 methods for class 'linkres'.

#### Description

Functions for printing, summarizing and plotting the results of a linkage analysis.

#### Usage

```
## S3 method for class 'linkres'
print(x, ...)
## S3 method for class 'linkres'
summary(object, ...)
## S3 method for class 'linkres'
plot(
  х,
  chrom = NULL,
  type = "1",
  1wd = NA,
 ylim = NULL,
 xlab = NULL,
 ylab = NULL,
  . . .
)
## S3 method for class 'linkres'
points(x, chrom = NULL, type = "1", lwd = NA, ...)
```

#### Arguments

x, object A linkres object (normally produced by lod() or merlinLod()).

4

| •••             | further arguments.  |
|-----------------|---|
| chrom           | (Optional) A numeric indicating which chromosomes to be included in the plot. |
| lwd, type, ylim | Graphical parameters passed on to plot().                                     |
| xlab,ylab       | Axis labels.  |

#### Value

These functions are called for their side effects.

#### See Also

lod(), merlinLod(), lodPeaks()

#### Examples

# Pedigree with 5 simulated SNP markers x = nuclearPed(3) x = setMarkers(x, alleleMatrix = cbind( m1 = c("1/1", "1/2", "1/2", "1/2", "1/2"), m2 = c("1/2", "1/2", "1/2", "1/2", "1/2"), m3 = c("1/1", "1/2", "1/2", "1/2", "1/1")), sep="/") # Mother and all children affected aff = c(1, 2, 2, 2, 2) # LOD scores under autosomal dominant model lods = lod(x, aff, model = diseaseModel(model = "AD")) summary(lods) as.data.frame(lods) plot(lods)

lod

#### Singlepoint LOD score

#### Description

Calculates the singlepoint log of the odds (LOD) scores of a pedigree for the specified markers, assuming a fixed recombination rate between the disease and each marker locus.

#### Usage

lod(
 x,
 aff,
 model,

6

```
rho = 0,
liability = NULL,
markers = NULL,
maxOnly = NA,
loopBreakers = NULL,
peelOrder = NULL,
verbose = FALSE
)
```

#### Arguments

| х            | A ped object.  |
|--------------|--|
| aff          | A vector naming the affected pedigree members, or a numeric vector of length $pedsize(x)$ with affection statuses for all pedigree members (2 = affected; 1 = unaffected; 0 = unknown). Alternatively, aff can be a list of vectors, named affected, unaffected and unknown. It suffices to give (any) two of these vectors. |
| model        | A disModel object, typically created with diseaseModel().  |
| rho          | A number between 0 and 0.5 (inclusive); the hypothesised recombination ratio between the marker and the disease locus.   |
| liability    | NULL (default) or a vector of length pedsize(x) indicating the liability class (a row number of model\$penetrances) of each individual.  |
| markers      | A vector of marker names or indices referring to markers attached to x. By default all markers are included.   |
| maxOnly      | a logical indicating whether only the maximum LOD score should be returned.<br>By default this is always done if the number of markers is 1.   |
| loopBreakers | A vector of ID labels indicating loop breakers. (Only relevant for inbred pedi-<br>grees.)   |
| peelOrder    | For internal use.  |
| verbose      | a logical: verbose output or not.  |
|              |  |

#### Details

The LOD score of a marker is defined as

$$LOD(\rho) = \log \frac{L(\rho)}{L(0.5)}$$

where the logarithms are base 10, and  $L(\rho)$  denotes the likelihood of the observed marker genotypes given a recombination ratio  $\rho$  between the marker and the disease locus.

The likelihoods are computed with the **pedprobr** package.

#### Value

If the number of markers is 1, or if maxOnly = TRUE, a single number is returned.

Otherwise a linkres object, which is basically a data frame with columns CHROM, MARKER, MB and LOD.

#### lodPeaks

#### Author(s)

Magnus Dehli Vigeland

#### See Also

linkres, merlinLod(), diseaseModel(), lodPeaks()

#### Examples

```
x = nuclearPed(2) |>
addMarker(geno = c("1/2", "1/1", "1/2", "1/2"))
aff = c(2,1,2,2)
model = diseaseModel(model = "AD")
lod(x, aff, model)
```

lodPeaks

LOD score peaks

#### Description

Identify and summarise LOD score peaks.

#### Usage

```
lodPeaks(x, threshold, width = 1)
```

peakSummary(x, threshold, width = 1, physmap = NULL)

#### Arguments

| х         | A linkres object, or data frame with columns CHROM, MB, LOD.                              |
|-----------|---|
| threshold | A single number   |
| width     | A positive integer  |
| physmap   | A matrix or data frame with three columns: Marker name, chromosome and physical position. |

#### Details

A peak is defined as a run of at least width consecutive markers with LOD score above or equal to threshold. If possible, one flanking marker is included on each side of the peak.

#### Value

A list of data frames.

#### See Also

linkres, lod(), merlinLod()

#### Examples

merlinLod

Multipoint LOD scores by MERLIN

#### Description

This function is a wrapper for the parametric linkage functionality of the MERLIN software. For this to work, MERLIN must be installed and correctly pointed to in the PATH environment variable.

#### Usage

```
merlinLod(
    x,
    aff,
    model,
    map = NULL,
    markers = NULL,
    rho = 0,
    liability = NULL,
    maxOnly = NA,
    options = "",
    dir = tempdir(),
    cleanup = TRUE,
    verbose = FALSE,
    ...
```

```
)
```

#### Arguments

| aff | A vector naming the affected pedigree members, or a numeric vector of length     |
|-----|--|
|     | pedsize(x) with affection statuses for all pedigree members (2 = affected; 1)    |
|     | = unaffected; $0 =$ unknown). Alternatively, aff can be a list of vectors, named |

| affected, unaffected and unknown. It suffices to give (any) two of these vectors.   |
|---|
| A disModel object, typically created with diseaseModel().   |
| A data frame with columns according to MERLIN format for map files.   |
| A vector of marker names or indices referring to markers attached to x. By default all markers are included.  |
| A numeric with values between 0 and 0.5: The recombination value(s) for which the LOD score is computed. The value of rho is converted to centiMorgans using Haldane's map function and included in the MERLIN command using theposition parameter. |
| Note: This parameter only works when markers has length 1.  |
| NULL (default) or a vector of length pedsize(x) indicating the liability class (a row number of model\$penetrances) of each individual.   |
| a logical indicating whether only the maximum LOD score should be returned.<br>By default this is always done if the number of markers is 1.  |
| A character with additional options to the MERLIN command.  |
| Path to a directory where the MERLIN input files should be created.   |
| A logical indicating if MERLIN files should be removed after use. Default: TRUE.  |
| a logical: verbose output or not.   |
| Further arguments passed on to pedprobr::merlin(). In particular, merlinpath should be supplied if the merlin executables are not on the system's search path.  |
|   |

#### Details

By default the following MERLIN command is run (via a call to system()) after creating appropriate files in a temporary (or user specified) directory:

\_merlin.freq --model \_merlin.model --tabulate --markerNames --quiet

The resulting multipoint LOD scores are extracted from the output and returned in R as a linkres object.

#### Value

If the number of markers is 1, or if maxOnly = TRUE, a single number is returned.

Otherwise a linkres object similar to the output of lod(), but with an additional column CM.

#### References

https://csg.sph.umich.edu/abecasis/merlin/

#### See Also

lod()

#### Examples

```
#------
# Requires MERLIN to be installed
#------
if(pedprobr::checkMerlin()) {
# Pedigree with a single marker
x = nuclearPed(3, sex = c(1,2,2)) |>
addMarker(geno = c("1/1", "1/2", "1/2", "1/2", "1/2"))
# Simple AD model
merlinLod(x, aff = 2:5, model = diseaseModel("AD"))
# With liability classes
mod = diseaseModel("AD", penetrances = cbind(f0 = 0, f1 = 1:0, f2 = 1:0))
merlinLod(x, aff = 2:4, mod, liability = c(1,1,1,1,2))
# X
merlinLod(x, aff = 3:5, model = diseaseModel("XR"))
}
```

10

# Index

\* datasets dominant1, 3diseaseModel, 2diseaseModel(), 6, 7, 9 dominant1, 3 linkres, 4, 7–9 lod, 5 lod(), 2-5, 8, 9 lodPeaks,7 lodPeaks(), 5, 7 merlinLod, 8 merlinLod(), 4, 5, 7, 8 peakSummary (lodPeaks), 7 pedprobr::merlin(),9 pedtools::ped, 3 plot.linkres(linkres),4 points.linkres(linkres),4 print.linkres(linkres),4

summary.linkres(linkres),4
system(),9